




### Dimensions



### Specifications

<b>Standard materials</b>	Valve body	Aluminium
	Sealing element	Brass disc
	Seals	Viton/Silicone
	Solenoid housing	Plated steel/Stainless steel/Aluminium
<b>Net weights</b>	Standard solenoid actuated	3 lbs (1.4 kg)
<b>Intake air temp range</b>	Standard valve	-40°C to 125°C (-40°F to 257°F)
<b>Ambient air temp range</b>	Standard valve	-40°C to 125°C (-40°F to 257°F)
<b>Electric solenoid actuation</b>	Nominal 12 VDC power requirement	48 amp pull in
	Cycle rate	4 activations per minute
	Nominal 24 VDC power requirement	25 amp pull in
	Cycle rate	6 activations per minute

### How to Order

MODEL SVR - **A** - **B**

A	Actuation
281	2" 12V Electric
291	2" 24V Electric

B	Hose Diameter
44	44 MM hose
48	48 MM hose
51	51 MM hose
57	57 MM hose
60	60 MM hose
64	64 MM hose

### Accessories for Fully Automatic Systems

Part No.	Description
1520-001	Revguard 2 Speed Switch
AK2-E1-RM-CH	Activation Kit for 12V Valve
AK2-E2-RM-CH	Activation Kit for 24V Valve

Contact our sales offices below for more information or to find your local distributor, visit our website and select "Find Local Distributor".

#### Americas

AMOT - USA  
Tel +1 (281) 940 1800  
Fax +1 (713) 559 9419  
sales@amot.com

Roda Deaco - Canada  
Tel +1 (780) 465 4429  
Fax +1 (780) 469 6275  
info@rodadeaco.com

#### Asia Pacific

AMOT - China  
Tel +86 21 6279 7700  
Fax +86 21 5237 8560  
shanghai@amot.com

AMOT - Singapore  
Tel +65 6408 6265  
Fax +65 6293 3307  
singapore@amot.com

#### Europe, Middle East and Africa

Chalwyn - England  
Tel +44 (0) 1284 715739  
Fax +44 (0) 1284 760256  
sales@chalwyn.com

AMOT - Germany  
Tel +49 (0) 40 8537 1298  
Fax +49 (0) 40 8537 1331  
germany@amot.com

[www.chalwyn.com](http://www.chalwyn.com)